




Made in the USA

2 year limited warranty

- Heavy duty solid spun discs with rolled edges
- Low profile riser & open drum slot
- Industrial grade brass, full flow swivel
- Permanently sealed pillow block bearings
- One piece ALL CNC robotically welded

100 Series "Challenger"



Lightweight, compact, versatile reels that perform at working pressures to 4000 PSI. Save time and effort while increasing the safety of your work environment. The sturdy "U" shaped frame and all steel construction make this one tough little reel.

- 4000 PSI maximum
- 225° F. maximum
- Adjustable friction brake
- Viton swivel seals

Part	Cox Part	Hose	Dimensions
4988	112-3-100	100'	18x13x12
4990	117-3-250	250'	18x18x17
2974	117-3-400	400'	22x18x17

Replacement Parts



Part	Cox Part	Product
4063	6329-1-1	Brake bearing EPDM
5977	1935	3/8FPT Brass Swivel
5993	1935seal	Swivel repair 1935

1125 Series "Competitor"

Has features demanded by industry professionals.



Solid steel crank smooth handle
Long handled lock pin secures reel
Adjustable friction brake

- 90° 1/2" FPT swivel
- 4000 PSI maximum
- 225°F. maximum

Part	Cox Part	3/8" Hose	W	H	L
4869	1125-4-200	300'	25½	18¾	17¾
6980	1125-4-325	450'	31½	18¾	17¾

Replacement Parts



Part	Cox Part	Product
4129	7429-4	Drag Brake
5344	439	Brass 1/2" swv
5979	439SEAL	Repair kit
2615	Locking pin	Assembly

Portable Hose Reel Cart



Pictured with competitor hose reel sold separate

1125 SERIES two wheeled cart. Ideal for grounds maintenance in restaurants, hotels, schools.

FEATURES:

- Steel handle detaches for storage
- Steel front legs with rubber feet prevent reels from slipping forward when pulling hose

Part	Product
4868	Hose reel cart only



Hose reels not included

1125 Series Stacking Bracket

Stack your hose reels for double the storage in the same work area. Steel construction, power coated crinkle black. Weight 6 lbs.

Part	Product
4892	For 1125-4-200 reel
4885	For 1125-4-325 reel

CM Series Caddy Mount

"Caddy Mount" hand crank hose reel is perfect for carrying the extra long lengths of hose to the job site. Hose control bar prevents the hose from slipping off the side discs and makes it easy to grab.



Part	Hose Max	WxHxL
5320	100'	18 x 13 x 13



Hose Reels



5431



5924



5355

Direct hand crank rewind with locking mechanism. Solid steel construction with durable powder-coat paint and full flow swivel.

- Industrial grade reel
- Maximum 4000 PSI
- Extend hose life
- Mount on wall, bench
- 225°F maximum

Part	Hose	In/Out	Ht	Wid
5355	50'	3/8" MPT x 3/8FPT	12.5	13
5430	100'	3/8" FPT x 3/8FPT	10.5	12.5
5431	150'	3/8MPT x 3/8FPT	13.5	10
5924	200'	3/8MPT x 3/8FPT Compact	16.5	10

Replacement Parts



5429



5428



Part	Product
4255	Handle Assembly w/screws
5429	Swivel 3/4 M27MST & 3/8 FPT in, 3/8FPT out 4000 PSI max.
5428	Swivel. 1/2 M x 3/8 F 4000 PSI
6782	Swivel kit 5428 & 5429
6753	Swivel o-ring kit 5428 & 5429
2603	Hi temp swivel kit 5428 & 5429



Swivel Hose Reels

- Reel swivels 200°
- Adjustable friction brakes
- Easy push/pull lock pin
- Smooth radius bent arm
- Heavy cold rolled metals
- 1/2" FPT in/out
- 4000 PSI 250°F

Slide-In

Part	Size
5700	K01-2024 100 ft
5718	K01-0206 200 ft

Drop-In

Part	Size
5701	K01-2025 100 ft.
5719	K01-0207 200 ft

Wall Mount

Part	Size
5707	K01-2027 100 ft
5728	K01-0208 200 ft

Flat Surface Mount

Part	Size
5709	K01-2028 100 ft
5729	K01-0209 200 ft

Mount Block

Easy mount adapter mounts to any round or square tubing

Part	Size
5702	K01-2026 100 ft



Universal Hose Reel Swivel

- 8 GPM maximum
- 3000 PSI maximum
- 300°F. maximum

Part	Size
1778	Adams 1/2FPT I/O
1779	Repair kit



JE Adams 90° Swivels

- Swivels under pressure
- 200°F. maximum
- 7 GPM maximum
- 3/8MPT x 3/8FPT

Part	Size	PSI
2295	Stainless Steel	5000
2608	Brass	3000
2294	Repair kit 2295	



Spring Rewind

A heavy duty spring motor provides self-contained rewind power. A non sparking ratchet assembly locks the reel when the desired length has been paid out



- 100' of 3/8" hose
- 1/2" Inlet/outlet
- 3000 PSI maximum
- 225°F. maximum
- 26" high 6" reel width
- 131 lbs ship weight

Be sure to specify the roller position when ordering. If roller position is NOT specified, reels will be shipped with rollers in the POSITION SR.



Position SR
Swivel joint right

Position TR
Swivel joint left

Position VR
Swivel joint right

Hose stop & hose sold separately

Ships via common carrier. Allow 2 weeks lead time

Part	Roller Position
6628	SR
6655	TR
6654	VR
5435	HS-3 hose stop



Compact design and quality steel construction.

- Complete with **Super Swivel®** for maximum delivery
- Full flow shaft and swivel for maximum delivery
- Lock pin prevents spool rotation when not in use
- Standard, durable, abrasion resistant, red baked powder coat



- 2 year limited warranty
- ISO 9001 certified
- 1/2" I/O

Spring Driven Reel

- 5000 PSI maximum
- 100 feet 3/8" hose
- 8" wide reel
- 25" High
- 325°F. maximum
- 81 lbs.



Hose stop & hose sold separately

Non stock item. Ships common carrier

Part	Hose Max
6884	PW81000 OHP
4324	Hose Stop



Hand Crank

- 3000 PSI maximum
- 325°F. maximum
- 100 feet 3/8" hose
- 15" wide reel
- 20" High
- 31 lbs.

Part	Model
4901	18006M

