



Genuine Pump Oil

Series 100
30 weight non detergent.
Specifically formulated for use
in high pressure plunger pumps



Part	Product
4021	Case 6- 16 oz
5864	Case 24-16oz
4022	16 oz bottle



6100 Original Pump Oil

Cat Pumps custom blend crankcase oil is exclusively designed, tested and proven to maximize the life of your Cat Pump. This special formulated premium grade, petroleum based, ISO 68 hydraulic oil contains the most advanced additive to protect against wear, oxidation, rust and corrosion



Part	Product
4019	Case 12-21 oz
4020	21 oz bottle
5711	5 gal. twin pak



Triplex Pump Oil

Specially formulated crankcase oil for high pressure pumps. contains anti-wear, rust inhibitors and deoxidizer additives. Forms a barrier that prevents metal to metal contact. Reduces friction and wear. Change oil after 50 hours of use, then every 500 hours.



Part	Item
6602	AR64516 Case 12-16 oz.
6603	16oz bottle

Synthetic Pump Oil

Specifically formulated for the XJ, SJV, RM, and BK pump series. DO NOT CHANGE OIL. Use oil only to add if low.



Part	Item
2787	AR64545 Case 24-4.5oz
6601	4.5 oz. bottle



Pump Oil

Specially formulated for use in all high pressure industrial piston pumps. Universal transmission oil (UTTO). 30 wt. non detergent and non-foaming. AW100 rated for superior oxidation protection.



Part	Item
6969	Case 12-32 oz
6970	32 oz. bottle

Beacon Pump Lube

API 10w30 non-detergent
ISO VG 68



Part	Product
5710	Case 12 32 oz
1753	32 oz bottle



Packing Extraction Kit

Comes with handy carrying case, and includes a slide hammer, 13mm, 15mm, 18mm, 20mm, 22mm, and 24mm sockets.

Part	Product
4030	Extraction kit
4012	Slide hammer head
4029	13mm socket
3640	15mm socket
4084	16mm socket
4194	18mm socket
4041	20mm socket
5936	22mm socket
5378	24mm socket
1628	Carry Case
1189	Socket screw
3859	Slide pin



Note: complete slide hammer order parts 4012, 1189, and 3859

Packing Insertion Kit

Plastic insertion tools for reassembly of packings. Kit includes 20mm, 22mm & 24mm.

Part	Product
4341	Insertion kit



Maintenance Meter

For 1 or 2 cylinder gasoline engines. Use to allow regular preventive maintenance. Benefit with increased fuel economy, less down time, and longer engine life.



3 FUNCTIONS:

- Hour Meter:** records actual running time of engine. Non-erasable.
- Service Alert:** Warns when lube & oil change is needed in 25 hour intervals. Will flash for 2 hours while engine runs.
- Tachometer:** Displays RPM up to 9,000 RPM.

Part	Product
4188	Maintenance meter

Engine Throttle Control

Save wear and tear on pump and engine. Reduce engine speed in bypass mode. Returns to full operating RPM immediately when pump operation resumes.



Part	Product	PSI
4723	Z Speed Throttle	3000
1660	Throttle Control	4000