



Please pay attention to RPM, voltage ratings and shaft size. If you are not sure ask for assistance while ordering

**Single Phase, Rigid Base, C-Face Open Drip Proof (ODP)**

2548



- Ball bearing design
- Manual thermal overload in conduit box
- UL & CSA recognized component approval
- 200°C. copper windings

Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
2548	PCL1319M	5/8"	56C	1.5	1725	115/230	14/7	46
2549	PCL1313M	5/8"	56C	1.5	3450	115/230	13/7	38
2550	PCL1322M	5/8"	56C	2.0	1725	115/230	18/9	48
2551	PCL1317M	5/8"	56C	2.0	3450	115/230	17/8.8	45
2552	CL1408TM	1-1/8"	184TC	3.0	1725	115/230	32/16	82
2553	PCL1326M	5/8"	56C	3.0	3450	230/208	13/12	50
2554	PCL1327M	5/8"	56HCY	5.0	3450	230	23	58
3329	Special	3/4"	56C	5.0	3450	230	23	58
2555	CL1410TM	1-1/8"	184TC	5.0	1725	230/208	23/25	91

3329



**Single Phase, Rigid Base, C-Face Totally Enclosed, Fan Cooled (TEFC)**

3123



Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
3122	PCL3514M	5/8"	56C	1.5	1725	115/230	12/6	53
3121	PCL3513M	5/8"	56C	1.5	3450	115/230	13/7	41
3123	PCL3515M	5/8"	56C	2.0	3450	115/230	18/9	46
3126	CL3619TM	1-1/8"	184TC	3.0	1725	230	13.2	84
3125	PCL3519M	5/8"	56C	3.0	3450	230/208	13/12.5	55
3128	CL3612TM	1-1/8"	184TC	5.0	1725	230	23	104
3127	CL3608TM	1-1/8"	184TC	5.0	3450	230	19.5	94

**3 Phase TEFC Motors**

3128



Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
2664	CEM3615T	1-1/8"	184TC	5.0	1750	208/230/460	13/7	81

**Rigid Base for Belt Drive units**



Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
5251	EM3770T	1-3/8"	213T	7.5	1760	230/460	25/12.5	176
5252	EM3774T	1-3/8"	215T	10.0	1760	230/460	25/12.5	204

**Motors Made ready (MMR)**



Motors pre-wired with switch, 36' cord and ground fault

Part	Baldor	Type	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
3120	PCL1319M	ODP	5/8"	56C	1.5	1725	115/230	14/7	46
3173	PCL1313M	ODP	5/8"	56C	1.5	3450	115/230	13/7	38
2654	PCL1322M	ODP	5/8"	56C	2.0	1725	115/230	18/9	48
2474	PCL1317M	ODP	5/8"	56C	2.0	3450	115/230	17/8.8	45
3201	PCL3514M	TEFC	5/8"	56C	1.5	1725	115/230	12/6	53
5270	PCL3513M	TEFC	5/8"	56C	1.5	3450	115/230	13/7	41
3584	PCL3515M	TEFC	5/8"	56C	2.0	3450	115/230	18/9	46

Motor pre-wired with cam switch and 10-3 20 foot cord only

Part	Baldor	Type	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
3332	Special	ODP	3/4"	56C	5.0	3450	230	23	58