

SUTTNER  **ST-1100 Lightweight**

Perfect for cold water units or smaller hot water units

- 7 GPM
- 3050 PSI
- 300°F. Max
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4126	ST-1100



MTM407

- 7 GPM maximum
- 4000 PSI maximum
- 250°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6150



HPC **740 Gun**

- 7 GPM maximum
- 4000 PSI maximum
- 250°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Product
6912	740 gun
6502	Kit



MV920 Karcher Style Gun

- 7 GPM max
- 4000 PSI max
- 300°F. Maximum
- 22mm male in/out

Part	Product
6069	MV920



ST-810 Front Entry

Front inlet design keeps dirty hose away from operator.

- 8 GPM maximum
- 3050 PSI maximum
- 320°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
1479



mecline  **MV2005**

- 8 GPM maximum
- 4000 PSI maximum
- 300°F. Maximum
- 3/8FPT inlet
- 1/4FPT outlet

Part	Model
6110	MV2005
6109	Kit



ST-1500H Open Gun

Ideal when unloader is unavailable

- 12 GPM maximum
- 4000 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1291	ST1500H



YRL51 Gun

- 13.2 GPM maximum
- 4050 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6267



5030 Gun

- 12 GPM maximum
- 4500 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1740	5030
1733	Kit



RL30/YG5000 Gun

Trigger design easier pull at high pressures
Larger, more comfortable hand grip space
To accommodate gloves

- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4855	RL30/YG5000
6228	Repair kit



VEGA/YG4000 Gun

Easy trigger pull
Ergonomically designed hand guard

- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
3452	VEGA
3450	Kit



Spray Guns

Excellent choice for heavy industrial applications.

- 10 GPM maximum
- 5000 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model	Outlet
1480	21250B	SS
2341	21290C	Steel
1632	Repair kit	



SPRAY GUNS

SUTTNER ST-1500 Top Seller



- Streamline designed to be “universally” Comfortable, even for very small hands
- Unitized valve for easy repair
- Stainless steel spring, needle, ball, and seat for chemical resistance
- 10.4 GPM max
- 5000 PSI max
- 300°F max
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
1475	ST-1500
1528	Kit 4000 PSI
5106	Kit 5000 PSI

ST-1500W Weep Gun



Most popular gun for self service car wash applications

Weep allows water to continue flowing after trigger is released. Prevents gun freeze

- 12 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
2324	ST-1500W
2325	Kit 4000 PSI

ST-2000 Big Hand Gun



- Ideal for rental machines
- Easy access to replace cartridge valve
- Takes the heat and abuse
- Easy access to replace cartridge valve

- 10.4 GPM max
- 5000 PSI max
- 300°F max
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
1477	ST-2000
1528	Kit 4000
5106	Kit 5000

ST-2305 Easy Pull!!!

The SUTTNER exclusive trigger, reduces Trigger opening force by up to 60% compared to all other rear entry spray guns.



- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
4654	ST-2305
4540	Repair kit

ST-2305 Safety Orange Cover!!

The SUTTNER exclusive trigger, reduces Trigger opening force by up to 60% Compared to all other rear entry spray guns.



- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6955	ST-2305
4540	Repair kit

ST-2605 Relax Action

- True over center cam
- Relax action™ trigger reduces pulling force by 40%
- Easiest opining and holding trigger in it's class
- Relax Action™ is designed for operators and applications with longer periods of cleaning time
- Unitized valve for easy repair



- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4539	ST-2605
4540	Repair kit
6792	Ceramic ball kit

DG5010 Spray Gun



- 10 GPM maximum
- 5000 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Product
6906	Gun
6917	Kit

KEW Style Spray Gun



With bayonet coupler and plug on outlet

- 10 GPM maximum
- 5000 PSI maximum
- 300°F maximum

Part	Model
6907	KEW w/coupler & plug
6123	Coupler replacement
6140	Plug replacement
6917	Gun repair kit

Stainless Steel Guns

SUTTNER ST-2700

- Stainless steel internal components.
- Suitable for corrosive chemical usage
- "Relax action" trigger and comfort grip
- Unitized valve for easy repair

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
4730	ST2700SS
5609	Standard Repair kit
6792	Ceramic Ball Kit

ST-3300

Highest **volume** rated industrial gun.

- Forged stainless steel housing, piston, and seat.
- Special heat and chemical resistant seals
- 27 GPM maximum
- 1/2" FPT inlet
- 2170 PSI maximum
- 1/2" FPT outlet
- 300°F. Maximum



Part
6708

ST-3600 Gun

- Forged stainless steel housing, piston, seat.
- Special heat and chemical resistant seals
- Suttner's highest **pressure** rated industrial gun.

- 21 GPM maximum
- 1/2" FPT inlet
- 8700 PSI maximum
- 1/2" FPT outlet
- 300°F maximum



ST-3600 Lance

- Perfect fit for the ST3600 gun
- Stainless steel construction
- Adjustable handle

- 1/2" MPT inlet
- 1/4" FPT outlet

Part	Product
6714	Gun
6732	39" Lance

High Volume, Low Pressure Guns

YG1732/RL124 Heavy Duty

- Construction of stainless steel & brass
- Trigger operation minimizes fatigue
- 32 GPM maximum
- 1/2" FPT inlet
- 1740 PSI maximum
- 1/2" FPT outlet
- 210°F maximum



Part	Product
3481	Gun

High Volume, Low Pressure Guns

SUTTNER ST2620

- For high volume, low pressure machines!
- Hold trigger open with one finger
- Easiest opening & holding trigger in class

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Part
6936	ST2620
4540	Repair Kit

ST2720 Stainless Steel

Ideal for high volume, low pressure applications such as food processing! Stainless steel valve components create a durable, long lasting gun

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Part
6937	ST2720
5609	Repair Kit

Chemical Resistant Guns

SUTTNER ST-810 POM

Front entry gun is the best chemical application gun with a stainless steel spring, needle, ball and a poly seat for chemical resistance

- 8 GPM maximum
- 2000 PSI maximum
- 320°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part
6561

ST-2315 w/Ceramic Ball

Ceramic ball in valve is highly resistant against nearly all soaps and acids. Suttner exclusive "relax-action trigger"

- 12 GPM maximum
- 5000 PSI maximum
- 300°F. Maximum
- 3/8" FPT maximum
- 1/4" FPT maximum



Part	Model
6916	ST2315 Gun
6792	Ceramic Ball Kit

SPRAY GUNS

Chemical Resistant Guns



YG5000C Gun

Ceramic ball for use with chlorine & acid

- Forged brass body with stainless wetted parts
- Trigger lock to prevent accidental activation



- 10.5 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6418	YG5000C
6425	Repair kit

Polypropylene Gun

- 18 GPM maximum
- 400 PSI maximum
- 1/2" FPT inlet
- 1/2" FPT outlet
- Stainless steel spring



Part
3826

Plastic Low Pressure Guns

To be used for chemical pre spray, or to spray acids.



- 2 GPM maximum
- 150 PSI maximum
- 100°F. Maximum

Part	Model
4494	Spraying system 1/4" FPT inlet 15"
1633	Spraying Systems 3/8" hose barb inlet
2201	Cone jet angled assembly (4494, 1633)

Linear/Straight Guns

SUTTNER ST-601



Heavy duty impact trigger guard makes ST-601 an industry standard for telescopic wand manufacturers.

Ideal for cleaning vertical & overhead surfaces.

- 12 GPM maximum
- 4000 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
2396	ST-601
1528	Repair kit



YG4500S

Straight spray gun. Insulated handle remains cool at maximum fluid temperature



- 10.5 GPM maximum
- 4500 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6967	YG4500S
6968	Repair kit

Specialty Gun/Lance Combos

Quick connect plug on inlet

Lance extension w/ quick connect socket on outlet



- 7 GPM maximum
- 4000 PSI maximum
- 300°F. Maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6843	Gun W/ 24" lance
6273	Gun w/ 36" lance
5889	Gun w/ 48" lance

MV2009 Rear Entry w/Extension



5529

- One piece
- 6.5 GPM maximum
- 3200 PSI maximum
- 22mm outlet
- 195°F. Maximum

Part	Model
5527	3/8" FPT Inlet
5539	22mm Male Inlet

Hobby Hose, Gun, Lance Kits

- 1/4"x22mmx22mm hose
- 1piece gun 22mm I/O w/12" ext.
- Additional 18" pipe extension



5418

- 6.6 GPM maximum
- 3000 PSI maximum

Part	Product
6132	Kit w/QC outlet
5418	Kit w/3.5 hi-lo nozzle
6081	Lance w/3.5 hi-lo nozzle

ST1500 w/Bendable-Wand



- ST-10 nozzle protector
- 2250 PSI maximum

Part
6826

RLW40 Dump Gun

Excellent for car washes



NOTE: Trigger will not pull unless under pressure

- 10.5 GPM maximum
- 3050 PSI maximum
- 140°F. Maximum
- 3/8" FPT inlet
- 1/8" FPT outlet

Part	Model
1046	16"
2375	40"
2376	Kit