



**Thermal Relief Valve**

- Protects pump from damaging heat build up while it is in the bypass mode.
- Quickest response to rising temperature
- 100 PSI

Part	GP No.	Inlet	Temp
3596	100556	1/4"mpt	145°F
3597	100557	3/8"mpt	145°F
5919	100679	3/8"mpt	190°F
3598	100558	1/2"mpt	145°F
5920	100680	1/2"mpt	190°F



**Rupture Disk**

Protects coil from over heating. 225°F. maximum



Part	Description
6987	1/2mpt inlet x 3/8 mpt outlet



**Safety Relief Valves**

1,000 to 6,000 PSI adjustable 195° F. max.

Part	GP No.	Inlet
5413	100728	1/4"mpt
5871	100534	3/8"mpt
2177	100729	1/2"mpt
2867	100724 w/barb	1/4"mpt
3301	100723 w/barb	3/8"mpt
2185	100722 w/barb	1/2"mpt



**Pressure Relief Valves**

- Made in USA
- Adjustable
- 10 GPM maximum
- 150° F. maximum

Part	PSI	Inlet
2507	500-1200 (Silver)	1/4"mpt
2322	1200-2400 (Red)	3/8"mpt
1889	2400-3600 (Orange)	3/8"mpt
2323	3600-5000 (Blue)	3/8"mpt



**Fluid Control Pressure Valves**

- 10 GPM maximum
- 150° F. maximum



Part	Model	PSI	Inlet
1292	RV-100	650-1500	1/4"mpt
3129	RV-500	900-2000	3/8"mpt
3130	RV-500	1900-3500	3/8"mpt
3485	RV-500 w/barb	900-2000	3/8"mpt
3486	RV-500 w/ barb	1900-3500	3/8"mpt

**Brass Check Valves**

Part	Size	PSI	Temp
3447	1/4"fpt	1200	180°F
3448	3/8"fpt	1200	180°F
3449	1/2"fpt	1200	180°F
2327	1/4"fpt	3000	200°F
2328	3/8"fpt	3000	200°F



**Stainless Steel Check Valves**



Part	Size	GPM	PSI	Temp
5593	1/4"fpt	6.5	6500	195°F
1991	3/8"fpt	10.5	6500	195°F

**In-line Thermostats**

- Positive in-line bimetal control
- 1/2" FPT I/O ports
- Universal 1/4" spade terminal connect
- 100 volt 25 amp



Part	Temp
1442	60° to 230°F
1443	60° to 340°F



**Remote Thermostat**

Remote probe thermostat is a capillary tube thermostat that relies on expansion of a viscous liquid to open and close switch.

- Panel mounted dual scale
- 60" insulated capillary tube
- UL/CSA approved
- 4000 PSI maximum



Part	GP No.	Temp
3942	100438	86° to 194°F
6712	100538	86° to 250°F
3943	100439	86° to 302°F

**High Limit Switches**

- Mounts in high pressure line senses overheating
- Responds by opening a n/c switch
- 110 volt 25 amp
- Can be used on 12 volt units

Part	Temp	Probe	Size
3914	176°F	Silver	3/8mpt
1444	230°F	Yellow	3/8mpt
4533	320°F	Red	3/8mpt
3915	176°F	Silver	1/2mpt
3665	203°F	Blue	1/2mpt
1440	230°F	Yellow	1/2mpt
1441	320°F	Red	1/2mpt



**With 60" Wire Lead (2 wire)**

Part	Temp	Probe	Size
3454	230°F	Yellow	3/8mpt
4216	230°F	Yellow	1/2mpt
5806	320°F	Red	1/2mpt





**Easy Start Valves**

Eliminates back pressure when pulling a manual start gas engine

- 1/4" hose barb outlet
- 3/8" MPT inlet

Part	Mfg.	GPM	PSI
5621	MTM	7.0	4100
2394	PA	8.0	4500
5998	General	8.0	5000

**SUTTNER ST-35R Strainer**



High volume suction strainer ideal for tank transfer or agricultural markets. Impact resistant plastic housing  
Stainless steel screen  
Brass weight to hold in place  
1/2" and 3/4" hose barb

Part	Product
2380	ST-35R

**Accumulators**

All accumulators are drop shipped from our vendors and ship via ground only

Accumulators are designed to extend the life of your pressure washer pump by reducing the pulsations that arise in the incoming water supply. The nitrogen filled accumulators absorb the "shock" of low water pressure instead of your pumps pistons, valves and packing.

**GIANT Accumulator**



- Precharged to 800 PSI
- 12 GPM maximum
- 2700 PSI maximum
- 1/2" MPT
- Rebuildable
- Stainless Steel casing

Hazmat charge applies

Part	Product
2407	Giant 22050A

**Hypro Suction Line**



50 mesh nylon screen with male garden hose outlet

Part
4096

**Chemical Strainers**



Part	Product
6538	Heavy wt. brass w/check valve
3675	Brass w/check valve ss screen
6431	4' Clear vinyl hose w/det. filter
1059	5' Polybraid hose w/det.filter
1285	Black plastic with check valve
5558	Black plastic no check valve
6233	Gray plastic with check valve
6264	Gray plastic no check valve
3446	ZF2 plastic w/check valve w/ stainless steel screen



**Accumulator**



- Zinc plated steel construction
- 10 GPM maximum
- 1300 PSI maximum
- Factory pre-charge 90-200 PSI air
- 3/4" FPT inlet
- Rebuildable

Vendor drop ship charge applies

Part
2406

**High Pressure Accumulator**

Non-Rechargeable



- 10 GPM maximum flow rate
- 60-3000 PSI operating pressure
- 1/2" FPT inlet
- Factory pre-charge 580 PSI nitrogen

Part
3104

**Tank Screens**



Part	Product
2990	1/4" fpt 50 mesh
2496	3/8" fpt 50 mesh
2497	1/2" fpt 50 mesh
2498	3/4" fpt 50 mesh

**Brass "Y" Strainer**



Part	Product
1286	1/2" brass SS screen
1287	3/4" brass SS screen
5758	1" brass SS screen



**SUTTNER ST-8 Float Valves**

Part	Size
1712	1/2" fpt 5GPM
1721	1/2" mpt adapter



**Brass Float Valves**

Part	Size
6994	1/2" mpt
6995	3/4" mpt
1571	Repair kit



**Brass Float Valve**

Includes bulkhead gasket and lock nut

Part	Size
6991	3/8" mpt
6992	1/2" mpt
6993	3/4" mpt



**Brass Float Valve**

Part	Size	GPM
2344	3/8" mpt	7.0



**Plastic Float Valve**



Part	Size	GPM
1019	3/4" mpt	8.0

**Float & Valve Rods**

Part	Size
5389	Poly float 5" long
1547	1/4"-20 x 2" rod
1548	1/4"-20 x 8" rod



**Float Tank w/Lid**

- 1 gallon capacity
- 5"W x 10.5"L x 8.5"H
- With baffle

Part	Product
1018	Plastic float tank

